



Kemo Electronic GmbH

Mato Vukovic
 Leher Landstr. 20
 27607 Geestland
 Germany

Phone: +49 4743 9338-0
 Fax: +49 4743 9338-22

<http://www.kemo-electronic.de>
 email: info@kemo-electronic.de

HR.Nr. HRB 111 486
 UstNr: DE 814 380 369

M176 - Marten Defence for Motor Vehicles 12 V/DC, splash-proof with IP 65*



Chases away the marten through high-voltage plates (movable) charged electrically to approx. 200 - 300 V/DC through electric shock in the motor compartment of the vehicle (only weak current pulses that merely chase the marten away but do not kill it) and through strong, aggressively pulsating ultrasonic sounds. Extremely low current consumption ($< 0.005\text{ A}$), switches off automatically at a battery voltage of $< 11.5\text{ V/DC}$ (does not discharge the battery if vehicles are being parked for quite some time). The basic device with the ultrasound radiation is splash-proof according to IP 65* and may be mounted directly at the vestibule opening of the marten in the car. Built-in brightly blinking LED.

Available accessories:

M038N - DC-Converter

Z115 - "Ground"-Mat for electroshock devices

Z176 - Extension-set 2 highvoltage plates for M176

This clip only shows that the module is waterproof, it is not suitable for permanent use under water.

Technical Data:

Features: splash-proof | 3-fold effectiveness: ultrasound, electric shock, pulsating light

Operating voltage: 12 - 15 V/DC (car battery)

Sealing: The control unit including the loudspeaker is splash-proof according to IP 65* (it can be mounted at the entrance holes of the motor vehicle.)

Average power consumption: $< 5\text{ mA}$

Switch-on function: soft start so that the vehicle computer will not be disturbed

Automatic switch-off: if the battery voltage decreases to $< 11,5\text{ V} (\pm 5\%)$

Output voltage: approx. 200 - 300 V/DC

Ultrasonic frequency: approx. $22\text{ kHz} \pm 10\%$

Acoustic pressure: max. approx. $100\text{ dB} \pm 20\%$ (Ultrasonic devices should have a sound pressure level exceeding 100 dB (C) to avoid habituation (ADAC test results). (Source <http://de.wikipedia.org/wiki/Marderabwehr>)

Angle of radiation ultrasound: approx. 160°

Loudspeaker: impact sound generator, which makes the upper side of the case oscillate (splash-proof)

Sound: sine, aggressively pulsating

Temperature range: approx. -25°C to $+80^\circ\text{C}$

Functional display: flashing LED (approx. every 5 - 12 sec.)

Cable length high-voltage cable: approx. 4 m ($\pm 10\%$)

Fuse in the fuse holder: 1 A

High-voltage contact plates: 6 pieces, movable, approx. 62 x 42 mm each, stainless steel

Dimensions basic device: approx. 40 x 50 x 70 mm (without cable entry + fastening feet)

Cable for terminal 15: If this cable is connected with „Positive“, the marten defence disconnects. The marten defence switches on if it is connected with „Negative“ or does not receive any signal.

CAN data bus: suitable for vehicles with CAN data bus.

Voltage peaks: The device is protected against voltage peaks in the vehicle power supply up to 40 V ($< 20\text{ ms}$).

Optical deterrent: The built-in pulsating LED unsettles the nocturnal martens in addition.

Why does the device have no frequency change? Answer: Martens and other small predators emit short and intense warning cries, no siren sounds! Our anti-marten device imitates these tones very naturally and is, therefore, optimal to scare away martens.

**Kemo Electronic GmbH**

Mato Vukovic
 Leher Landstr. 20
 27607 Geestland
 Germany

Phone: +49 4743 9338-0
 Fax: +49 4743 9338-22

<http://www.kemo-electronic.de>
 email: info@kemo-electronic.de

HR.Nr. HRB 111 486
 UstNr: DE 814 380 369

*IP65: No penetration of dust at a low pressure of 20mbar in the case. Protected against hose water from any direction against the case (corresponds to 12.5 ltr./minute – garden hose) (test period: 5 minutes)

**M176**