12 August 2025

Kemo Electronic GmbH Mato Vukovic Leher Landstr. 20 27607 Geestland Germany

Phone: +49 4743 9338-0 Fax: +49 4743 9338-22

http://www.kemo-electronic.de email: info@kemo-electronic.de

HR.Nr. HRB 111 486 UstNr: DE 814 380 369

## FG022 - Marten Repeller mobile

## This mobile marten repellent operates with latest high-frequency technology (ultrasound) and without assembly work. This marten repellent may be employed everywhere (e.g. in cars, carports, garages and houses), ideal as protection for e.g. cars that are parked for longer periods. The optimum maintenance-free time of performance of 12 months can only be reached with high-quality alkaline manganese batteries ( $2 \times 1.5 \vee$ Mignon AA, not enclosed). Of course, the device has to be mounted in such a way that no water or dirt may penetrate into the case. May also be used against mice and other rodents.

 $\frac{\text{Technical Data:}}{\text{Range of Action:}} > 55 \text{ m}^2$ 

GEL GERMANY #FG022 Destroys 0802001

Frequency: approx. 24 kHz (± 15%) Acoustic pressure: approx. 100 dB (± 20%) (Ultrasonic devices should have a sound pressure level exceeding 100 dB (C) to avoid habituation (ADAC test results). (Source <a style="color:#845;" href="http://de.wikipedia.org/wiki/Marderabwehr">de.wikipedia.org/wiki/Marderabwehr">de.wikipedia.org/wiki/Marderabwehr">de.wikipedia.org/wiki/Marderab wehr</a>)

Operating voltage: 3 V/DC Acoustic range: > 6 m





