

**Kemo Electronic GmbH**

Mato Vukovic
 Leher Landstr. 20
 27607 Geestland
 Germany

Phone: +49 4743 9338-0
 Fax: +49 4743 9338-22

<http://www.kemo-electronic.de>
 email: info@kemo-electronic.de

HR.Nr. HRB 111 486
 UstNr: DE 814 380 369

M206 - Flasher for LED or Incandescent Lamps 9 - 48 V/DC max. 10 A



You may connect either incandescent lamps or LED lamps with operating voltages ranging from 9 to 48 V/ DC to the flasher. The flasher is then operated at the operating voltage of the connected lamps. The device is short-circuit proof. Adjustable flash period: approx. 0.15 - 7 sec.

Technical Data:

Operating voltage: 9 - 48 V direct-current voltage (depending on the connected lamps)
 Current-carrying capacity: max. 10 amperes (at 12 V these are e.g. lamps up to max. 120 W)
 Adjustable flash period: approx. 0.15 - 7 sec.
 Light-pause ratio: approx. 50/50%
 Own current consumption: $\emptyset < 2.5$ mA
 Dimensions of the module: approx. 87 x 60 x 33 mm
 Display at the module: flashing LED
 Connections: mounting tabs 6.3 mm
 Short-circuit proof